

Paris-rue-Madame database: a 3D mobile laser scanner dataset for benchmarking urban detection, segmentation and classification methods

Andrés Serna¹, Beatriz Marcotegui¹, François Goulette² and Jean-Emmanuel Deschaud²

¹MINES ParisTech, CMM-Center for mathematical morphology, 35 rue St Honoré, 77305 Fontainebleau, France

²MINES ParisTech, CAOR-Center for robotics, 60 boulevard Saint-Michel, 75272 Paris, France

{andres.serna_morales, beatriz.marcotegui, francois.goulette, jean-emmanuel.deschaud}@mines-paristech.fr

Keywords: 3D database, mobile laser scanner, urban analysis, segmentation, classification, point-wise evaluation.

Abstract: This paper describes a publicly available 3D database from the rue Madame, a street in the 6th Parisian district. Data have been acquired by the Mobile Laser Scanning (MLS) system L3D2 and correspond to a 160 m long street section. Annotation has been carried out in a manually assisted way. An initial annotation is obtained using an automatic segmentation algorithm. Then, a manual refinement is done and a *label* is assigned to each segmented object. Finally, a *class* is also manually assigned to each object. Available classes include facades, ground, cars, motorcycles, pedestrians, traffic signs, among others. The result is a list of (*X*, *Y*, *Z*, *reflectance*, *label*, *class*) points. Our aim is to offer, to the scientific community, a 3D manually labeled dataset for detection, segmentation and classification benchmarking. With respect to other databases available in the state of the art, this dataset has been exhaustively annotated in order to include all available objects and to allow point-wise comparison.

1 INTRODUCTION

Nowadays, LiDAR technology ("light detection and ranging") has been prospering in the remote sensing community thanks to developments such as: Aerial Laser Scanning (ALS), useful for large scale buildings survey, roads and forests; Terrestrial Laser Scanning (TLS), for more detailed but slower urban surveys in outdoor and indoor environments; Mobile Laser Scanning (MLS), less precise than TLS but much more productive since the sensors are mounted on a vehicle; and more recently, "stop and go" systems, easy transportable TLS systems making a trade off between precision and productivity.

Thanks to all these technologies, the amount of available 3D geographical data and processing techniques has bloomed in recent years. Many semi-automatic and automatic methods aiming at analyzing 3D urban point clouds can be found in the literature. It is an active research area. However, there is not a general consensus about the best detection, segmentation and classification methods. This choice is application dependent. One of the main drawbacks is the lack of publicly available databases allowing benchmarking.

In the literature, most available urban data consist in close-range images, aerial images, satellite images but a few laser datasets (ISPRS, 2013; IGN, 2013).

Moreover, manual annotations and algorithm outputs are rarely found in available 3D repositories (Nüchter and Lingemann, 2011; CoE LaSR, 2013).

Some available data include Oakland dataset (Munoz et al., 2009), which contains 1.6 million points collected around Carnegie Mellon University campus in Oakland, Pittsburgh, USA. Data are provided in ASCII format: (*X*, *Y*, *Z*, *label*, *confidence*) one point per line, vrml files and label counts. The training/validation and testing data contains 5 labels (scatter misc, default wires, utility poles, load bearing and facades). Ohio database (Golovinskiy et al., 2009) is a combination of ALS and TLS data in Ottawa city (Ohio, USA). It contains 26 tiles 100 × 100 meters each with several objects such as buildings, trees, cars and lampposts. However, ground truth annotations only consists in a 2D labeled point in the center of each object. In that sense, segmentations results cannot be evaluated point by point. Enschede database (Zhou and Vosselman, 2012) contains residential streets approximately 1 km long in the Enschede city (The Netherlands). Ground truth annotation consists in 2D geo-referenced lines marking curbstones. A well-defined evaluation method is available using buffers around each 2D line. The drawback of this dataset is that no other objects are annotated. Paris-rue-Soufflot database (Hernández

Figure 2 presents one of the 3D point clouds of this database colored by the point height (Z coordinate), the *reflectance*, the object *label* and the object *class*.




Figure 2: “GT_Madame1.2.ply” file: 3D point cloud colored by its available fields. For the object *label*, each color represents a different object (only for visualization purposes, some colors have been repeated). For object *class* visualization: facades (blue), ground (gray), cars (yellow), motorcycles (olive), traffic signs (goldenrod), pedestrians (pink).

This database contains 642 objects categorized in 26 classes, as shown in Table 1. It is noteworthy that several objects inside buildings have been acquired through windows and open doors, these objects have been annotated as facades. Other several “special” classes have been added because they are too different to be mixed with others. For instance, *fast pedestrians* and *pedestrians+something* have different geometrical features than a simple pedestrian. The idea of this annotation is including as much classes as possible, then each user may gather or exclude classes depending on the application.

It is noteworthy that this database is different from

Table 1: Available classes and number of objects in the Paris-Rue Madame dataset.

Class	Class name	Number of objects	
		file 1.2	file 1.3
0	Background	7	35
1	Facade	181	117
2	Ground	4	23
4	Cars	39	31
7	Light poles	0	1
9	Pedestrians	3	7
10	Motorcycles	23	9
14	Traffic signs	5	1
15	Trash can	2	1
19	Wall Light	6	1
20	Balcony Plant	3	2
21	Parking meter	1	1
22	Fast pedestrian	2	2
23	Wall Sign	1	3
24	Pedestrian + something	1	0
25	Noise	46	80
26	Pot plant	0	4
Total		324	318

others available in the state of the art since the entire 3D point cloud has been segmented and classified, i.e. each point contains a label and a class. Thus, point-wise evaluation of detection, segmentation and classification methods is possible.

4 ACQUISITION

The acquisition has been carried out by the MLS system L3D2 from the robotics laboratory CAOR-MINES ParisTech (Goulette et al., 2006). This system is equipped with a Velodyne HDL32, as shown in Figure 3. In this system, several lasers are mounted on upper and lower blocks of 32 lasers each and the entire unit spins, giving much denser point clouds than classic Riegl sensors (Velodyne, 2012).



Figure 3: MLS system L3D2 from CAOR-MINES ParisTech

5 ANNOTATION

Annotation has been carried out in a manually assisted way. An initial segmentation is obtained using an automatic method based on elevation images (Serna and Marcotegui, 2013b). The work-flow is shown in Figure 4. For further details and complete analyses in each step, the reader is also encouraged to review the following three works (Hernández and Marcotegui, 2009) (Serna and Marcotegui, 2013a) (Serna and Marcotegui, 2013c).




Figure 4: Work-flow of our automatic segmentation methodology.


After this automatic method, a manual refinement is carried out in order to correct possible errors in detection and segmentation steps. Then, a *label* is assigned to each segmented object. Finally, a *class* is also manually assigned in order to categorize each segmented object.

During manual refinement, three typical segmentation errors are both found and corrected: i) bad segmentation of some connected objects, e.g. motorcycles parked close to each other are not correctly separated, as shown in Figure 5; ii) over-segmentation of some objects due to artifacts or noise, i.e. some cars are over-segmented on their roof, as shown in Figure 6; iii) sub-segmentation of some objects, i.e. some objects touching the facades are not well separated, as shown in Figure 7.


6 DOWNLOAD & LICENSE

Paris-rue-Madame database is available at: <http://cmm.ensmp.fr/~serna/rueMadameDataset.html> and it is made available under the Creative Commons Attribution Non-Commercial No Derivatives (CC-BY-NC-ND-3.0) Licence.

(Cette œuvre est mise à disposition selon les termes



(a) Height



(b) Automatic segmentation (zoomed) (c) Manual refinement (zoomed)

Figure 5: Manual refinement of connected motorcycles.

de la Licence Creative Commons Attribution - Pas d'Utilisation Commerciale - Pas de Modification 3.0 France <http://creativecommons.org/licenses/by-nc-nd/3.0/fr/>).

7 CONCLUSIONS

We have presented a 3D MLS database manually annotated from rue Madame, a street in the 6th Parisian district. Each 3D point has been labeled and classified, resulting in a list of (X , Y , Z , *reflectance*, *label*, *class*) points.

The database has been acquired by the L3D2 vehicle, a MLS system from the Robotics laboratory (CAOR) at MINES ParisTech. A distinctive feature of this system is that it uses a Velodyne sensor aligned in a similar way to a Riegl sensor but providing much




Figure 6: Manual refinement of over-segmented cars.

denser 3D point clouds.

Annotation has been carried out in a manual assisted way by the Center for mathematical morphology (CMM) at MINES ParisTech. First, an automatic segmentation method is applied. Then, manual refinement and classification are done. This approach is faster than a completely manual approach and it provides accurate results. This dataset is different from others available in the state of the art since each point has been segmented and classified, allowing point-wise benchmarking.

In future works, other datasets acquired in the framework of TerraMobilita project will be annotated and made available to the scientific community.




Figure 7: Manual refinement of sub-segmented objects touching the facade.

ACKNOWLEDGEMENTS

The work reported in this paper has been performed as part of Cap Digital Business Cluster TerraMobilita Project.

REFERENCES

- CoE LaSR (2013). *Centre of Excellence in Laser Scanning Research*. Finnish Geodetic Institut. <http://www.fgi.fi/coelasr/> (Last accessed: December 16, 2013).
- Golovinskiy, A., Kim, V., and Funkhouser, T. (2009). Shape-based recognition of 3D point clouds in urban

- environments. In *IEEE International Conference on Computer Vision*, pages 2154–2161. Kyoto, Japan.
- Goulette, F., Nashashibi, F., Ammoun, S., and Laugeau, C. (2006). An integrated on-board laser range sensing system for On-the-Way City and Road Modelling. *The ISPRS International Archives of Photogrammetry, Remote Sensing and Spatial Information Sciences*, XXXVI-1:1–6.
- Hernández, J. and Marcotegui, B. (2009). Filtering of artifacts and pavement segmentation from mobile LiDAR data. *The ISPRS International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, XXXVIII-3/W8:329–333.
- IGN (2013). *IGN - Geospatial and Terrestrial Imagery*. IGN French National Mapping Agency. http://isprs.ign.fr/home_en.htm (Last accessed: October 28, 2013).
- ISPRS (2013). *The ISPRS data set collection*. ISPRS International Society for Photogrammetry and Remote Sensing. <http://www.isprs.org/data/> (Last accessed: October 28, 2013).
- Munoz, D., Bagnell, J. A., Vandapel, N., and Herbert, M. (2009). Contextual Classification with Functional Max-Margin Markov Networks. In *IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR)*.
- Nüchter, A. and Lingemann, K. (2011). *Robotic 3D Scan Repository*. Jacobs University Bremen gGmbH and University of Osnabrück. <http://kos.informatik.uni-osnabrueck.de/3Dscans/> (Last accessed: December 16, 2013).
- Serna, A. and Marcotegui, B. (2013a). Attribute controlled reconstruction and adaptive mathematical morphology. In *2013 International Symposium on Mathematical Morphology (ISMM)*, pages 207–218, Uppsala, Sweden.
- Serna, A. and Marcotegui, B. (2013b). Detection, segmentation and classification of 3D urban objects using mathematical morphology and supervised learning. *{ISPRS} Journal of Photogrammetry and Remote Sensing*, 0(0):1–. (Accepted).
- Serna, A. and Marcotegui, B. (2013c). Urban accessibility diagnosis from mobile laser scanning data. *ISPRS Journal of Photogrammetry Remote Sensing*, 84:23–32.
- Velodyne (2012). *The HDL-32E Velodyne LiDAR sensor*. Velodyne Lidar 2012. <http://velodynelidar.com/lidar/hdlproducts/hdl32e.aspx> (Last accessed: December 16, 2013).
- Zhou, L. and Vosselman, G. (2012). Mapping curbstones in airborne and mobile laser scanning data. *International Journal of Applied Earth Observation and Geoinformation*, 18(1):293–304.